

PE/N-support (01 356)



Description

Article

Part No.: 01 356

PE/N-support

2-pole, indiv. mountable

for busbars 12, 15, 20, 25, 30 x 5, 10

for busbars 12, 15, 20, 25, 30 x 5, 10

System

60Classic

Product group 06

Subgroup 06

pack size 10

EAN 4021267013561

Advantages of the product

With external screw holes, can also be used as centre support

5 / 10mm depth balancing possible, N-PE connection easy to make

Catalog page 2015 : 2/1

eCl@ss 6.1 27400607

eCl@ss 7.1 27400607

ETIM 4.0 EC001166

ETIM 5.0 EC001166

Approvals

Standards

IEC 61439-1:2011

Approvals

UL



for UL feeder circuits >250V

Type number: S356-L

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

CCC approval: no certification required

Product data

Electrical data

Rated voltage (IEC) AC: 690
V

Rated voltage (UL) AC: 600
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 0 W.

(The power dissipation for operation with rated current would be 0 W.)

Rated surge voltage U_{imp} : 6 kV
max. permitted voltage (IEC) AC: 1000
V
max. permitted voltage (IEC) DC: 1500
V

UL :
SCCR = 14 kA (Schienenträger im Abstand von 400 mm)

Mechanical data

W x H x D: 20 x 164 x 50
Weight: 9.5 kg/100
Poles: 2-pole
for busbars: 12, 15, 20, 25, 30 x 5, 10

Material properties

Main temperature stability 125°C,
body: self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free
Screws: screw +/- (PZ2), galvanized, chromized

Accessories



01 325

end cover

for busbar support 01 356 and 01 601