



# Compression Fittings

RECOMMENDED FOR USE WITH *JetTubes™* (see page 18)

**DIMENSIONS IN INCHES (except as noted)**

MALE CONNECTOR (includes nut and sleeve)							
Part No.	Tube Size	Thread "E"	Straight Thread (Nut End)	"C" Hex	L	Pkg Qty	Configuration
CF15510	3/16	1/16 NPT/BSPT	3/8 - 24 UN	7/16	1.08	5	
CF15470		1/8 NPT/BSPT		7/16	1.12	5	
CF15475		1/4 NPT/BSPT		9/16	1.15	5	
CF15530		M8x1.0		7/16*	1.10	5	
CF15535		M8x1.25		7/16	1.10	5	
CF15538		M10x1.0		7/16*	1.13	5	
CF15540		M10x1.25		7/16	1.13	5	
CF15545		M10x1.5		7/16†	1.13	5	
CF15524	1/4	1/16 NPT/BSPT	7/16 - 24 UN	7/16	1.15	5	
CF15480		1/8 NPT/BSPT		7/16	1.20	5	
CF15485		1/4 NPT/BSPT		9/16	1.25	5	
CF15487		3/8 NPT/BSPT		11/16	1.40	5	
CF15532		M8x1.0		7/16*	1.18	5	
CF15539		M10x1.0		7/16*	1.20	5	
CF15543		M10x1.25		7/16	1.20	5	
CF15548		M10x1.5		7/16†	1.20	5	
CF15554	M12x1.0	9/16*	1.20	5			
CF15552	M12x1.25	9/16	1.20	5			
CF15550	M12x1.75	9/16†	1.20	5			
CF15490	5/16	1/8 NPT/BSPT	1/2 - 24 UN	1/2	1.20	5	
CF15495		1/4 NPT/BSPT		9/16	1.25	5	
CF15497		3/8 NPT/BSPT		11/16	1.40	5	
CF15500	3/8	1/4 NPT/BSPT	9/16 - 24 UN	9/16	1.32	5	
CF15505		3/8 NPT/BSPT		11/16	1.44	5	

\* 2 Identifying notches on points of hex † 1 Identifying notch on points of hex

MALE ELBOW (includes nut and sleeve)							
Part No.	Tube Size	Thread "E"	Straight Thread (Nut End)	L	N	Pkg Qty	Configuration
CFE15712	3/16	1/8 NPT/BSPT	3/8 - 24 UN	.78	.62	5	<p><b>NOTE:</b> Thread "E" on all elbows, including metric threads, is tapered and tightens into mating port like a tapered pipe thread.</p>
CFE15734		1/4 NPT/BSPT		.86	.93	5	
CFE15806		M6x1.0*		.78	.62	5	
CFE15813		M8x1.0*		.78	.62	5	
CFE15826		M8x1.25		.78	.62	5	
CFE15854		M10x1.0*		.78	.62	5	
CFE15866		M10x1.25		.78	.62	5	
CFE15870		M10x1.5		.78	.62	5	
CFE15875	M12x1.0*	.78	.62	5			
CFE15723	1/4	1/8 NPT/BSPT	7/16 - 24 UN	.86	.62	5	
CFE15745		1/4 NPT/BSPT		.92	.75	5	
CFE15821		M8x1.0*		.86	.62	5	
CFE15833		M8x1.25		.86	.62	5	
CFE15862		M10x1.0*		.86	.62	5	
CFE15868		M10x1.25		.86	.62	5	
CFE15873		M10x1.5†		.86	.62	5	
CFE15887		M12x1.0*		.86	.62	5	
CFE15891	M12x1.25	.86	.62	5			
CFE15923	M12x1.75†	.86	.62	5			
CFE15726	5/16	1/8 NPT/BSPT	1/2 - 24 UN	.86	.62	5	
CFE15757		1/4 NPT/BSPT		.92	.75	5	
CFE15895		M12x1.25		.86	.62	5	
CFE15934		M12x1.75†		.86	.62	5	
CFE15761	3/8	1/4 NPT/BSPT	9/16 - 24 UN	.97	.75	5	
CFE15774		3/8 NPT/BSPT		1.03	.88	5	

\* 2 Identifying face grooves on square shoulder † 1 Identifying face groove on square shoulder

NUT						SLEEVE			
Part No.	Tube Size	Internal Thread	"C" Hex	Pkg Qty	Configuration	Part No.	Tube Size	Pkg Qty	Configuration
CF15410	3/16	3/8 - 24 UN	7/16	25		CF15430	3/16	25	
CF15420	1/4	7/16 - 24 UN	1/2	25					
CF15422	5/16	1/2 - 24 UN	9/16	25					
CF15424	3/8	9/16 - 24 UN	5/8	25					

Material: Brass Maximum Pressure: 500 PSI (33 bar) Maximum Operating Temperature: 300°F (150°C)

### Ordering Information

Determine the thread size and pitch of the ports on your machine. Order connectors and elbows to suit.  
Order spare nuts and sleeves to enable easy swapping of *JetTubes* without changing connectors.

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE OR OBLIGATION.